


HOHMANN & BARNARD, INC.
a MiTek company

Adjustable Reinforcement Systems

280 Dub'l Loop-Lok™ Ladder



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

280-BL Dub'l Loop-Lok Reinforcement w/Byna Lok™ Wire Tie

MATERIAL CONFORMANCE

Hohmann & Barnard joint reinforcement products conform to:
ASTM A951/A951M (Standard Specification for Steel Wire for Masonry Joint Reinforcement)
ACI / ASCE 530 (Building Code Requirements for Masonry Structures)

Wire (Carbon Steel): Prefabricated from cold-drawn steel wire conforming to **ASTM A1064/A1064M**
 Tensile Strength - 80,000 p.s.i. | Yield Point - 70,000 p.s.i. minimum
 Zinc Coating:
 Hot-Dip Galvanized after fabrication: **ASTM A153/A153M-B2** (1.5 oz/ft²)
 Note: Hohmann & Barnard will certify to a minimum of 2.0 oz/ft²

Wire (Stainless Steel): **ASTM A580/ASTM 580M** - AISI Type 304
 (Type 316 available on special order)

Wire Diameter:

9 gauge (.148" or W1.7)
 3/16" (.187" or W2.8)
 Side Rods and Cross Rods available in any combination of the above.
 Cross Rods welded 16" O.C. First Cross Rods welded 12" in from each end to allow lap splices per code requirements.
 Loops and Box Byna-Ties are 3/16"Ø.

H&B manufactures steel wire products from a minimum of 95% recycled material.

Finish:

- Hot-Dip Galvanized
- Stainless Steel-Type 304
- Stainless Steel-Type 316

Note: H&B recommends Stainless Steel for maximum protection against corrosion.

Wire Size (10' length standard, custom length available special order):

- (S) Standard Weight:
9 Gauge Side Rods x 9 Gauge Cross Rods
- (EH) Extra Heavy:
3/16"Ø Side Rods x 9 Gauge Cross Rods
- (SHD) Super Heavy Duty:
3/16"Ø Side Rods x 3/16"Ø Cross Rods

Block Size:

- | | | | |
|------------------------------|------------------------------|------------------------------|------------------------------|
| <input type="checkbox"/> 4" | <input type="checkbox"/> 6" | <input type="checkbox"/> 8" | <input type="checkbox"/> 10" |
| <input type="checkbox"/> 12" | <input type="checkbox"/> 14" | <input type="checkbox"/> 16" | |

Note: State cavity and/or insulation thickness when ordering.

- Optional Loop-Lok Washer to hold insulation to back-up
- Optional: Loop with 2¼" vertical adjustability.

IMPORTANT: Since each construction project is unique, the appropriate selection and use of any product contained herein must be determined by competent architects, engineers and other appropriate professionals who are familiar with the specific requirements of the project in question.

HOHMANN & BARNARD, Inc.
 30 Rasons Court | Hauppauge, NY 11788
 CORPORATE HEADQUARTERS
 T: 800.645.0616 F: 631.234.0683
www.h-b.com

Branch/Subsidiary Locations:
 ALABAMA - ILLINOIS - MARYLAND
 NEW YORK - PENNSYLVANIA - TEXAS
 UTAH - CANADA

© HOHMANN & BARNARD, INC. - 2015